

PRICE LISTS

SUGGESTED LIST PRICES

GASOLINE AND DIESEL BASIC ENGINES



KOHLER
ENGINES

EFFECTIVE SEPTEMBER 1, 2011

Contents

Description	Page
Gasoline Basic Engines.....	3-39
KOHLER Courage® XT	3-4
KOHLER Courage® Small Horizontal.....	5-6
KOHLER Courage® Single Cylinder.....	7
KOHLER Courage® Twin Cylinder	8
KOHLER Courage PRO®	9
KOHLER Command PRO® Vertical Shaft Engines.....	10-12
KOHLER Command PRO® Small Horizontal Shaft Engines	13-22
KOHLER Command PRO® Horizontal Shaft Engines.....	23-31
KOHLER Command PRO® EFI	32-33
KOHLER Command®	34-38
KOHLER Aegis®	39
Diesel Basic Engines.....	40-51
KOHLER® Diesel Air-Cooled.....	40-45
KOHLER® Diesel Liquid-Cooled.....	46-51
Evap Cross Reference Courage and Command.....	52-53

Prices shown are for Kohler Basic Engines. All other specification prices are available on request from Kohler Co. All prices are in U.S. Dollars, FOB factory, Kohler, Wisconsin, U.S.A., and are subject to change without notice. All engine specifications on this price list are subject to change without notice.

Gasoline engine horsepower ratings exceed Society of Automotive Engineers Small Engine Test Code J1940. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, and ambient operating conditions (temperature, humidity, and altitude). For more information, contact Kohler Co. Engine Engineering Department.

Diesel engine horsepower ratings are provided according to ISO 1585. The diesel automotive power rating is according to ISO 1585. Actual diesel engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, etc.), application, engine speed, and ambient operating conditions (temperature, humidity, and altitude). For more information, contact Kohler Co. Engine Engineering Department.


Miscellaneous Information:

1. All crankshafts rotate counterclockwise when viewed toward the PTO face.

KOHLER Courage[®] XT

XT-6 (Vertical Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve • Cast Iron Cylinder Bore • Flywheel Ball Upper Main Bearing • 149 cc Displacement • Net Peak Torque - 6.3 ft. lbs. @ 2600 rpm • Net Horsepower - 3.8 hp @ 3600 rpm • Splash Lubrication • Accu-Fill[™] Fuel Tank • 1.1 Liter Fuel Tank • ¼ Turn, Easy Access Extended Yellow Dipstick • Light Weight Flywheel for Lawnmowers • Fixed Speed @ 3100 rpm • Internally Vented Carburetor • Automotive Style Pleated Air Filter with Foam Precleaner • Flywheel Brake • Easy-Pull Recoil Starter with Ergonomic Handle • Smart-Choke[™], easy, no prime starting • Electronic Ignition • Front Exit Muffler with Guard • Internal Fuel Filter • Black Engine Cover and 6-position recoil • Resistive Spark Plug • Crankshaft - 25 mm Diameter x 3-5/32" PTO Length, 1/4" Full Key, 2 #505 Woodruff Slots, Drilled and Tapped 3/8"-24 UNF • SAE J609 Mounting Flange E (8" dia. BC) • EPA Phase II, CARB Tier II Exhaust Compliant • RFI Compliant 					
	3.8	XT-6	XT149-0201*		30
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-7/8" (22.225 mm) Diameter x 3 5/32" (80.1688 mm), 2-#505 Woodruff Key Slots, 3/16" Full Key, Drilled and Tapped 3/8"-24 UNF 					
	3.8	XT-6	XT149-0202*		30
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-7/8" (22.225 mm) Diameter x 3 5/32" (80.1688 mm), 2-#505 Woodruff Key Slots, 3/16" Full Key, Drilled and Tapped 3/8"-24 UNF • Electric Start • Side Discharge Muffler • Remote variable speed 1800-3300 rpm with choke and kill incorporated • Utility Model • No foam precleaner 					
	3.8	XT-6	XT149-0203*		30




Note: Contact your source of supply for pricing.

*Limited Quantity Available.

KOHLER Courage[®] XT

XT-7 (Vertical Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> Overhead Valve Cast Iron Cylinder Bore Flywheel Ball Upper Main Bearing 173 cc Displacement Net Peak Torque - 7.3 ft. lbs. @ 2600 rpm Net Horsepower - 4.8 hp @ 3600 rpm Splash Lubrication Accu-Fill[™] Fuel Tank 1.4 Liter Fuel Tank ¼ Turn, Easy Access Extended Yellow Dipstick Light Weight Flywheel for Lawnmowers Fixed Speed @ 3100 rpm Internally Vented Carburetor Automotive Style Pleated Air Filter with Foam Precleaner Flywheel Brake Easy-Pull Recoil Starter with Ergonomic Handle Smart-Choke[™], easy, no prime starting Electronic Ignition Front Exit Muffler with Guard Internal Fuel Filter Black Engine Cover and 6-position recoil Resistive Spark Plug Crankshaft - 25 mm Diameter x 3-5/32" PTO Length, 1/4" Full Key, 2 #505 Woodruff Slots, Drilled and Tapped 3/8"-24 UNF SAE J609 Mounting Flange E (8" dia. BC) EPA Phase II, CARB Tier II Exhaust Compliant RFI Compliant 					
	4.8	XT-7	XT173-3204*		30
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft-7/8" (22.225 mm) Diameter x 3 5/32" (80.1688 mm), 2-#505 Woodruff Key Slots, 3/16" Full Key, Drilled and Tapped 3/8"-24 UNF 					
	4.8	XT-7	XT173-3205*		30
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft-7/8" (22.225 mm) Diameter x 3 5/32" (80.1688 mm), 2-#505 Woodruff Key Slots, 3/16" Full Key, Drilled and Tapped 3/8"-24 UNF Heavy Flywheel for utility applications Remote Manual Choke Remote Variable Speed 1800-3300 rpm Remote low speed shutdown Side discharge muffler 					
	4.8	XT-7	XT173-3206*		30
Standard Features Plus:					
<ul style="list-style-type: none"> Stepped Blade Brake Clutch (BBC) Crankshaft Heavy Flywheel Ignition kill lead for remote shutdown 					
	4.8	XT-7	XT173-3207*		30




Note: Contact your source of supply for pricing.

*Limited Quantity Available

KOHLER Courage®

6.5 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> Overhead Valve Design Electronic Ignition Dual Element Air Cleaner (Unless otherwise mentioned) Dual Oil Fill Locations Dual Oil Drains Cast Iron Cylinder Liner 3.6 L Metal Fuel Tank with Strainer Fuel Shut-off Valve (Unless otherwise mentioned) Engine Mounted Throttle and Choke Controls, Remote Throttle Ready Oil Sentry™ Switch Installed (No Light) Dual Ball Bearings, PTO and Flywheel Metal Blower Housing Indexable Recoil Starter PTO Face <ul style="list-style-type: none"> For engines with SAE crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) 5/16-24 UNF-2B Thread. For engines with Metric crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) M8x1.25-6H Thread. Large Capacity Muffler w/Heat Shield Multi-Lingual Owner's Manual Color - Black with Cast Aluminum <u>Important Compliance Information:</u> <ol style="list-style-type: none"> Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can be sold globally) Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand) Specs containing -1XXX do not meet any compliance. These engine <u>cannot</u> be sold in US, Canada, EU, Australia and New Zealand (For sale in rest of the world) 					
					
Standard Features Plus:					
Variable Speed,					
Crankshaft - 0.75" (19.05 mm) Diameter x	6.5	SH265	SH265-0011		40
2.42" (61.47 mm) PTO Length,	6.5	SH265	SH265-1011		40
Tapped 5/16-24 UNF	6.5	SH265	SH265-3011		40
Standard Features Plus:					
Crankshaft - 20mm Diameter x 53mm PTO Length, Tapped M8 x 1.25-6H	6.5	SH265	SH265-0012		40
Standard Features Plus:					
Crankshaft - 3/4" Diameter x 2.38" PTO Length, Threaded Pump Shaft, Variable Speed	6.5	SH265	SH265-0013		40
	6.5	SH265	SH265-1013		40
Standard Features Plus:					
Crankshaft - 5/8" Diameter x 2.44" PTO Length, Threaded Pump Shaft, Variable Speed	6.5	SH265	SH265-0014		40
	6.5	SH265	SH265-1014		40
	6.5	SH265	SH265-3014		40


6.5 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO	6.5	SH265	SH265-0015		40
Length, w/2.25" per foot taper, Fixed Speed	6.5	SH265	SH265-1015		40
50 Hertz (3150 rpm HSNL),	6.5	SH265	SH265-3015		40
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO	6.5	SH265	SH265-0016		40
Length, w/2.25" per foot taper, Fixed Speed	6.5	SH265	SH265-1016		40
60 Hertz (3750 rpm HSNL)	6.5	SH265	SH265-3016		40
Standard Features Plus:					
• Variable Speed,					
• Crankshaft - 0.75" (19.05 mm) Diameter x 2.42" (61.47 mm) PTO Length, Tapped 5/16-24 UNF					
• Recoil and electric start with key box and 3 amp charging	6.5	SH265	SH265-0021		46
	6.5	SH265	SH265-3021		46
Standard Features Plus:					
• Variable Speed,					
• Crankshaft - 0.75" (19.05 mm) Diameter x 2.42" (61.47 mm) PTO Length, Tapped 5/16-24 UNF					
• Recoil and electric start with key box and 10 amp charging	6.5	SH265	SH265-0031		46
	6.5	SH265	SH265-3031		46
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot taper, Fixed Speed 50 Hertz (3150 rpm HSNL)					
• Low Profile Air Cleaner					
• No Fuel Tank, No fuel shut-off valve	6.5	SH265	SH265-0055		33
• No Muffler	6.5	SH265	SH265-1055		33
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot taper, Fixed Speed 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner					
• No Fuel Tank, No fuel shut-off valve	6.5	SH265	SH265-0056		33
• No Muffler	6.5	SH265	SH265-3056		33

Note: Contact your source of supply for pricing.

KOHLER Courage®

15, 16, 18, 20, 21, & 22 HP (Vertical Shaft) Single Cylinder


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none">• Overhead Valve Design• Twin Cam Design• Cross-Flow Cylinder Head• Inverted Crankcase• Dual Reciprocating Balance System• Ported Power Intake• Fuel Shutdown Solenoid• Electronic Ignition• Acoustically Dampened Air Induction• Full Pressure Lubrication• Oil Filter• Extended Oil Fill/Dipstick-Yellow• Pulse Fuel Pump• Cast-Iron Cylinder Liner• 15 Amp Regulated/Rectifier Charging• Governed Idle• Unitized Throttle and Choke Control• Variable Speed Governor• Large Capacity In-Line Fuel Filter• Automatic Compression Release• 12V Bendix Electric Starter• Crankshaft -1" (25.4 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF• PTO Face-10" (254 mm) Diameter, (4 Holes) 0.35" (8.9 mm) x 1" (25.4 mm) Deep					
					
Standard Features Plus:					
<ul style="list-style-type: none">• EVAP	15	SV470	SV470-3200	\$905.19	81
	21	SV610	SV610-3200	\$861.01	81
	22	SV620	SV620-3202	\$1,043.79	81
Standard Features Plus:					
<ul style="list-style-type: none">• RFI	20	SV600S	SV600-0202*	\$949.21	81
Standard Features Plus:					
<ul style="list-style-type: none">• RFI	16	SV480S	SV480-3202	\$950.46	81
<ul style="list-style-type: none">• EVAP	18	SV540S	SV540-3202	\$950.77	81
	20	SV600	SV600-3202	\$949.21	81

*Limited Quantity Available

KOHLER Courage.

22, 23, 24, 25, & 26 HP (Vertical Shaft) Twin Cylinder

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • 1.125" Diameter x 4.36" PTO Length, 7/16-20 Crankshaft • Cast-Iron Cylinder Liners • 10" D.B.C., 4 Cored Holes (For OEM Self-Tap) • Full Pressure Lubrication • Oil Filter • Automotive Style Dipstick (Yellow) • 7/16" External Square Oil Drain Plug • Stellite® Exhaust Valves • 12V Bendix Electric Starter • 15A Regulated Charging System • Digital Advance Ignition System (DSAI) - SV735 only • RFI/Ctick Compliance • Modulated Cooling Fan • Fixed Grass Screen Guard • Carburetor w/Fuel Shutdown Solenoid • Pulse Fuel Pump • 51 Micron Fuel Filter • Single Wire Controls - Throttle and Choke • Mechanical Governor • Torx Head Boden Screws • Dual Element Air Cleaner • Standard HP Decal (Black with Silver Lettering) • Engine Plate with Emission Certification • Governed Idle Speed 1750 (+150/-250) rpm • High Speed 3300 (+/- 75) rpm • Owner's Manual (English) • Color-Black with Cast Aluminum 					
Standard Features Plus:					
• EVAP	22	SV715	SV715-3001	\$1,066.10	106
	23	SV720	SV720-3001	\$1,083.37	106
	24	SV725	SV725-3001	\$1,083.13	106
	24	SV725	SV725-3002	\$1,058.06	106
	25	SV730	SV730-3001	\$1,081.74	106
	26	SV735	SV735-3001	\$1,113.94	106
	26	SV735	SV735-3002	\$1,101.65	106




KOHLER Courage PRO.

20, 23, 25, & 27 HP (Vertical Shaft) Twin Cylinder

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
-------------	----	-------	-----------	------------	------------------------

Standard Features:

- 1.125" Diameter x 4.36" PTO Length, 7/16-20 Hardened Crankshaft
- Cast-Iron Cylinder Liners
- 10" D.B.C., 4 Cored Holes (For OEM Self-Tap)
- Full Pressure Lubrication
- Large Capacity Oil Filter
- Automotive Style Dipstick (Yellow)
- 7/16" External Square Oil Drain Plug
- Stellite® Exhaust Valves
- 12V Bendix Electric Starter
- 15A Regulated Charging System
- Digital Advance Ignition System (DSAI) – SV840 only
- RFI/Ctick Compliance
- Modulated Cooling Fan
- Fixed Grass Screen Guard
- Carburetor w/Fuel Shutdown Solenoid
- Pulse Fuel Pump
- 51 Micron Fuel Filter
- Single Wire Controls - Throttle and Choke
- Mechanical Governor
- Torx Head Boden Screws
- Large Capacity Dual Element Air Cleaner
- Standard HP Decal (Black with Silver Lettering)
- Engine Plate with Emission Certification
- Governed Idle Speed 1750 (+150/-250) rpm
- High Speed 3300 (+/- 75) rpm
- Owner's Manual (English)
- Color-Black with Cast Aluminum



Standard Features Plus:


- EVAP

20	SV810	SV810-3001	\$1,099.80	106
23	SV820	SV820-3001	\$1,097.40	106
25	SV830	SV830-3001	\$1,097.25	106
27	SV840	SV840-3002	\$1,128.63	106

KOHLER Command PRO®

20-27 HP (Vertical Shaft) V-Twin


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Electronic Ignition • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Digital Spark Advance System (27 HP) • Large Capacity Dual Element Air Cleaner • Closed Breather System • High Efficiency Grass Screen and Fan • Stellite® Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Fill Tube and Dipstick-Yellow • Large Capacity Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired- Unconnected) • Canister Muffler with Heat Shield, Oil Filter Side Outlet • Variable Speed Governor • High Performance Accelerator Pump Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Pulse Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft (18-22 HP)-1" (25.4 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • Crankshaft (25-27 HP)-1.125" (28.5 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • PTO Face-10" (254 mm) Diameter, 4 Through Holes, 0.36" (9 mm) Diameter • Color-Black with Cast Aluminum 					
Standard Features Plus:					
• 3/16" Evaporative emissions connection	20	CV640	CV640-3002	\$1,690.04	108
	25	CV730	CV730-3101	\$1,987.36	108
	27	CV740	CV740-3001	\$2,145.16	100
Standard Features Plus:					
<ul style="list-style-type: none"> • Universal Commercial Mowing Replacement Engine • Special Chopper Grass Screen and Fixed Guard • No Exhaust System-Studs, Nuts, and Gaskets only • 3/16" Evaporative emissions connection 					
	23	CV680	CV680-3002	\$1,753.06	106



KOHLER Command PRO®

30 HP (Vertical Shaft) V-Twin


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Electronic Ignition • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Digital Spark Advance System • Heavy Duty Canister Air Cleaner System • Closed Breather System • High Efficiency Grass Screen and Fan • Stellite® Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Fill Tube and Dipstick-Yellow • Large Capacity Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired- Unconnected) • Canister Muffler with Heat Shield, Oil Filter Side Outlet • Variable Speed Governor • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Pulse Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft - 1.125" (28.5 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • PTO Face - 10" (254 mm) Diameter, 4 Through Holes, 0.36" (9 mm) Diameter 					
Color-Black with Cast Aluminum					
Standard Features Plus:					
<ul style="list-style-type: none"> • Special Chopper Grass Screen and Fixed Guard • Kohler HDAC • 3/16" Evaporative emissions connection 					
	30	CV750	CV750-3005	\$2,398.11	110



KOHLER Command PRO[®]

38 HP (Vertical Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Nylon Cam Gear • Cast-Iron Cylinder Liners • Stellite[®] Exhaust Valves • Flywheel and PTO Sleeve Bearings • Electronic Ignition • High Performance Spark Plugs RFI and EMC Compliant • Full Pressure Lubrication • Top Mount Spin-On Large Capacity Oil Filter • Large Dual Oil Drains • Heavy Duty Canister Air Cleaner System • High Efficiency Grass Screen and Fan • Fixed Grass Screen Guard • Blower Housing with Removable Cylinder Access Covers • Easy Access Dipstick and Oil Fill-Yellow • Oil Sentry[™] (Switch Installed but Unconnected) • Variable Speed Governor • Top Mounted Remote Controls (for boden wire connection) • Closed Breather System • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke[™] Carburetor • Pulse Fuel Pump • Large Capacity In-Line Fuel Filter • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft-1.125" (28.5 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • PTO Face-10" (254 mm) Diameter, (4 Holes) M8 x 1.25 • Canister Muffler with Heat Shield, Opposite Starter Side Outlet • Color-Black with Cast Aluminum 					
Standard Features Plus					
• 3/16" Evaporative emissions connection	38	CV980	CV980-2002	\$2,625.70	127




Exhaust System Kits

Kit/Part No.	Description	List Price
62 786 04-S	PTO Canister Muffler Kit-Center Outlet (Includes Muffler)	\$134.95
62 786 05-S	PTO Canister Muffler Kit-Starter Side Outlet (Includes Muffler)	\$134.95
62 786 06-S	PTO Canister Muffler Kit-Opposite Starter Side Outlet (Includes Muffler).....	\$134.95

KOHLER Command PRO®

7 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> Overhead Valve Design Electronic Ignition Quad-Clean™ 4-Stage All-Season Heavy Duty Cyclonic Air Cleaner (Unless otherwise mentioned) Dual Oil Fill Locations and Oil Drains Cast Iron Cylinder Liner 4.1 L Metal Tank w/Strainer Fuel Shut-off Valve (Unless otherwise mentioned) Stellite® Exhaust Valve Engine Mounted Throttle and Choke Controls, Remote Throttle Ready Oil Sentry™ Switch Installed (No Light) Dual Ball Bearings, PTO and Flywheel Metal Blower Housing Indexable Recoil Starter PTO Face <ul style="list-style-type: none"> For engines with SAE crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) 5/16-24 UNF-2B x 15 deep For engines with Metric crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) M8x1.25-6H x 15 deep Large Capacity Muffler w/Heat Shield and Spark Arrestor Multi-language Owner's Color - Black with Cast Aluminum <u>Important Compliance Information:</u> <ol style="list-style-type: none"> Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can be sold globally) Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand) Specs containing -1XXX do not meet any compliance. These engine <u>cannot</u> be sold in US, Canada, EU, Australia and New Zealand (For sale in rest of the world) 					
Standard Features Plus:					
• Crankshaft - 3/4" Diameter x 2.42" PTO	7	CH270	CH270-0011		45
Length, Straight Shaft w/Keyway, Variable	7	CH270	CH270-1011		45
Speed	7	CH270	CH270-3011		45
Standard Features Plus:					
• Crankshaft - 20mm Diameter x 53mm PTO	7	CH270	CH270-0012		45
Length, Straight Shaft w/Keyway, Variable	7	CH270	CH270-1012		45
Speed	7	CH270	CH270-3012		45
Standard Features Plus:					
• Crankshaft - 3/4" Diameter x 2.41" PTO	7	CH270	CH270-0013		45
Length, Straight Shaft w/Threads, Variable	7	CH270	CH270-1013		45
Speed	7	CH270	CH270-3013		45
Standard Features Plus:					
• Crankshaft - 5/8" Diameter x 2.44" PTO	7	CH270	CH270-0014		45
Length, Threaded Pump Shaft, Variable	7	CH270	CH270-1014		45
Speed	7	CH270	CH270-3014		45



7 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)	7	CH270	CH270-0015		45
	7	CH270	CH270-1015		45
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)	7	CH270	CH270-0016		45
	7	CH270	CH270-1016		45
	7	CH270	CH270-3016		45
Standard Features Plus:					
• Crankshaft - 20mm Diameter x 53mm PTO Length, Straight Shaft w/Keyway, Variable Speed	7	CH270	CH270-0017		45
• 2:1 Gear Reduction	7	CH270	CH270-3017		45
Standard Features Plus:					
• Crankshaft - 3/4" Diameter x 2.42" PTO Length, Straight Shaft w/Keyway, Variable Speed					
• Recoil and electric start with key box and 3 amp charging	7	CH270	CH270-0021		52
	7	CH270	CH270-3021		52
Standard Features Plus:					
• Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Recoil and electric start with key box and 3 amp charging	7	CH270	CH270-0025		52
Standard Features Plus:					
• Crankshaft - 3/4" Diameter x 2.42" PTO Length, Straight Shaft w/Keyway, Variable Speed					
• Recoil and electric start with key box and 10 amp charging	7	CH270	CH270-0031		52
	7	CH270	CH270-3031		52
Standard Features Plus:					
• Crankshaft - 20mm Diameter x 53mm PTO Length, Straight Shaft w/Keyway, Variable Speed					
• Recoil and electric start with key box and 10 amp charging	7	CH270	CH270-3032		52

7 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 3/4" Diameter x 2.41" PTO Length, Threaded Pump Shaft, Variable Speed Recoil and electric start with key box and 10 amp charging 	7	CH270	CH270-3033		52
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL) Recoil and electric start with key box and 10 amp charging 	7	CH270	CH270-0035		52
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3150 rpm HSNL) Low Profile Air Cleaner No Fuel Tank, No fuel shut-off valve No Muffler 	7	CH270	CH270-0055		37
	7	CH270	CH270-1055		37
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL) Low Profile Air Cleaner No Fuel Tank, No fuel shut-off valve No Muffler 	7	CH270	CH270-0056		37
	7	CH270	CH270-3056		37
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL) Low Profile Air Cleaner Recoil and electric start with key box and 3 amp charging No Fuel Tank, No fuel shut-off valve No Muffler 	7	CH270	CH270-0065		37
	7	CH270	CH270-1065		37
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL) Low Profile Air Cleaner Recoil and electric start with key box and 3 amp charging No Fuel Tank, No fuel shut-off valve No Muffler 	7	CH270	CH270-3066		37


7 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft - 0.78" Diameter x 2.82" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL) • Low Profile Air Cleaner • Recoil and electric start with key box and 10 amp charging • No Fuel Tank, No fuel shut-off valve • No Muffler 					
	7	CH270	CH270-3076		37

Note: Contact your source of supply for pricing.

KOHLER Command PRO®

9.5 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> Overhead Valve Design Electronic Ignition Quad-Clean™ 4-Stage All-Season Heavy Duty Cyclonic Air Cleaner (Unless otherwise mentioned) Dual Oil Fill Locations and Oil Drains Cast Iron Cylinder Liner 7 L Metal Tank w/Strainer Fuel Shut-off Valve (Unless otherwise mentioned) Stellite® Exhaust Valve Engine Mounted Throttle and Choke Controls, Remote Throttle Ready Oil Sentry™ Switch Installed (No Light) Dual Ball Bearings, PTO and Flywheel Balance Shaft Metal Blower Housing Indexable Recoil Starter PTO Face <ul style="list-style-type: none"> For engines with SAE crankshaft: 6.5" (165.1mm) Diameter Bolt Circle (4 Holes) 3/8-16 UNC thread x 0.71" deep and 5" (127 mm) Diameter Bolt Circle (4 + 2 Holes) 5/16-24 UNF threads x 0.71" deep For engines with metric crankshaft: 6.5" (165.1mm) Diameter Bolt Circle (4 Holes) 3/8-16 UNC thread x 0.71" deep and 5" (127 mm) Diameter Bolt Circle (4 + 2 Holes) M8 x 1.25-6H threads x 18mm deep Large Capacity Muffler w/Heat Shield and Spark Arrestor Multi-language Owner's Manual Color - Black with Cast Aluminum <u>Important Compliance Information:</u> <ol style="list-style-type: none"> Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can be sold globally) Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand) Specs containing -1XXX do not meet any compliance. These engine <u>cannot</u> be sold in US, Canada, EU, Australia and New Zealand (For sale in rest of the world) 					
					
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 7/16-20 UNF, Variable speed	9.5	CH395	CH395-0011		69
	9.5	CH395	CH395-1011		69
	9.5	CH395	CH395-3011		69
Standard Features Plus:					
• Crankshaft - 1" Diameter x 3.51" PTO Length, Threaded Pump Shaft, Variable Speed	9.5	CH395	CH395-0014		69
	9.5	CH395	CH395-1014		69
	9.5	CH395	CH395-3014		69
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)	9.5	CH395	CH395-0015		69
	9.5	CH395	CH395-1015		69
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)	9.5	CH395	CH395-0016		69
	9.5	CH395	CH395-3016		69

9.5 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 7/16-20 UNF, Variable speed					
• Recoil and electric start with key box and 3 amp charging	9.5	CH395	CH395-0021		82
	9.5	CH395	CH395-3021		82
Standard Features Plus:					
• Crankshaft - 1" Diameter x 3.51" PTO Length, Threaded Pump Shaft, Variable Speed					
• Recoil and electric start with key box and 3 amp charging	9.5	CH395	CH395-0024		82
	9.5	CH395	CH395-3024		82
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Recoil and electric start with key box and 3 amp charging	9.5	CH395	CH395-0025		82
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Recoil and electric start with key box and 3 amp charging	9.5	CH395	CH395-0026		82
	9.5	CH395	CH395-3026		82
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 7/16-20 UNF, Variable speed					
• Recoil and electric start with key box and 10 amp charging	9.5	CH395	CH395-0031		82
	9.5	CH395	CH395-1031		82
	9.5	CH395	CH395-3031		82
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 7/16-20 UNF, Variable speed					
• Recoil and electric start with key box and 18 amp charging	9.5	CH395	CH395-0041		82
	9.5	CH395	CH395-3041		82
Standard Features Plus:					
• Crankshaft - 25mm Diameter x 63.2 PTO Length, Variable speed					
• Recoil and electric start with key box and 10 amp charging	9.5	CH395	CH395-0032		82

9.5 HP (Horizontal Shaft) Single Cylinder


Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Low Profile Air Cleaner					
• No Fuel Tank, No fuel shut-off valve	9.5	CH395	CH395-0055		55
• No Muffler	9.5	CH395	CH395-1055		55
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner	9.5	CH395	CH395-0056		55
• No Fuel Tank, No fuel shut-off valve	9.5	CH395	CH395-1056		55
• No Muffler	9.5	CH395	CH395-3056		55
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Low Profile Air Cleaner					
• Recoil and electric start with key box and 3 amp charging					
• No Fuel Tank, No fuel shut-off valve	9.5	CH395	CH395-0065		64
• No Muffler	9.5	CH395	CH395-1065		64
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner					
• Recoil and electric start with key box and 3 amp charging					
• No Fuel Tank, No fuel shut-off valve					
• No Muffler	9.5	CH395	CH395-3066		64

Note: Contact your source of supply for pricing.

KOHLER Command PRO®

14 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> Overhead Valve Design Electronic Ignition Quad-Clean™ 4-Stage All-Season Heavy Duty Cyclonic Air Cleaner (Unless otherwise mentioned) Dual Oil Fill Locations and Oil Drains Cast Iron Cylinder Liner 7 L Metal Tank w/Strainer Fuel Shut-off Valve (Unless otherwise mentioned) Stellite® Exhaust Valve Engine Mounted Throttle and Choke Controls, Remote Throttle Ready Oil Sentry™ Switch Installed (No Light) Dual Ball Bearings, PTO and Flywheel Balance Shaft Metal Blower Housing Indexable Recoil Starter PTO Face <ul style="list-style-type: none"> For engines with SAE crankshaft: 6.5" (165.1mm) Diameter Bolt Circle (4 Holes) 3/8-16 UNC thread x 0.71" deep and 5" (127 mm) Diameter Bolt Circle (4 + 2 Holes) 5/16-24 UNF threads x 0.71" deep For engines with metric crankshaft: 6.5" (165.1mm) Diameter Bolt Circle (4 Holes) 3/8-16 UNC thread x 0.71" deep and 5" (127 mm) Diameter Bolt Circle (4 + 2 Holes) M8 x 1.25-6H threads x 18mm deep Large Capacity Muffler w/Heat Shield and Spark Arrestor Multi-language Owner's Manual Color - Black with Cast Aluminum <u>Important Compliance Information:</u> <ol style="list-style-type: none"> Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can be sold globally) Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand) Specs containing -1XXX do not meet any compliance. These engine <u>cannot</u> be sold in US, Canada, EU, Australia and New Zealand (For sale in rest of the world) 					
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 3/8-24 UNF, Variable Speed 	14	CH440	CH440-0011		87
	14	CH440	CH440-1011		87
	14	CH440	CH440-3011		87
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 1" Diameter x 3.51" PTO Length, Threaded Pump Shaft, Variable Speed 	14	CH440	CH440-0014		87
	14	CH440	CH440-1014		87
	14	CH440	CH440-3014		87
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL) 	14	CH440	CH440-0015		87
	14	CH440	CH440-1015		87
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL) 	14	CH440	CH440-0016		87
	14	CH440	CH440-3016		87
Standard Features Plus:					
<ul style="list-style-type: none"> Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 3/8-24 UNF, Variable Speed Recoil and electric start with key box and 3 amp charging 	14	CH440	CH440-0021		99
	14	CH440	CH440-3021		99



14 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 1" Diameter x 3.51" PTO Length, Threaded Pump Shaft, Variable Speed					
• Recoil and electric start with key box and 3 amp charging	14	CH440	CH440-0024		99
	14	CH440	CH440-3024		99
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Recoil and electric start with key box and 3 amp charging	14	CH440	CH440-0025		99
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Recoil and electric start with key box and 3 amp charging	14	CH440	CH440-0026		99
	14	CH440	CH440-3026		99
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 3/8-24 UNF, Variable Speed	14	CH440	CH440-0031		99
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-1031		99
	14	CH440	CH440-3031		99
Standard Features Plus:					
• Crankshaft - 25mm Diameter x 62mm PTO Length, Tapped M8 x 1.25 - 6H, Variable Speed					
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-0032		99
Standard Features Plus:					
• Crankshaft - 1" Diameter x 3.51" PTO Length, Threaded Pump Shaft, Variable Speed					
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-0034		99
	14	CH440	CH440-3034		99
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-0035		99
	14	CH440	CH440-1035		99
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-0036		99
	14	CH440	CH440-3036		99

14 HP (Horizontal Shaft) Single Cylinder

Description	HP	Model	Spec. No.	List Price*	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft - 1.0" (25.4 mm) Diameter x 3.49" (88.61 mm) PTO Length, Tapped 3/8-24 UNF, Variable Speed					
• Recoil and electric start with key box and 18 amp charging	14	CH440	CH440-0041		99
	14	CH440	CH440-3041		99
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Low Profile Air Cleaner					
• No Fuel Tank, No fuel shut-off valve	14	CH440	CH440-0055		81
• No Muffler	14	CH440	CH440-1055		81
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner	14	CH440	CH440-0056		81
• No Fuel Tank, No fuel shut-off valve	14	CH440	CH440-1056		81
• No Muffler	14	CH440	CH440-3056		81
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 50 Hertz (3150 rpm HSNL)					
• Low Profile Air Cleaner					
• Recoil and electric start with key box and 3 amp charging					93
• No Fuel Tank, No fuel shut-off valve	14	CH440	CH440-0065		93
• No Muffler	14	CH440	CH440-1065		
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner					
• Recoil and electric start with key box and 3 amp charging					
• No Fuel Tank, No fuel shut-off valve					
• No Muffler	14	CH440	CH440-3066		93
Standard Features Plus:					
• Crankshaft - 0.87" Diameter x 4.18" PTO Length, w/2.25" per foot Taper Shaft, Fixed Speed, 60 Hertz (3750 rpm HSNL)					
• Low Profile Air Cleaner					
• Recoil and electric start with key box and 10 amp charging	14	CH440	CH440-0076		93
• No Fuel Tank, No fuel shut-off valve	14	CH440	CH440-1076		93
• No Muffler	14	CH440	CH440-3076		93


Note: Contact your source of supply for pricing.

KOHLER Command PRO[®]

18-27 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Digital Spark Advance System (27 HP) • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) (25 & 27 HP) • Electronic Ignition • Large Capacity Dual Element Air Cleaner • High Efficiency Grass Screen and Fan • Closed Breather System • Stellite[®] Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Large Capacity Oil Filter, Dual Oil Drain • Oil Sentry[™] (Switch Installed and Wired but Unconnected) • Variable Speed Governor • High Performance Accelerator Pump Carburetor (25 & 27 HP) • Fuel Shutdown Solenoid, Smart-Choke[™] Carburetor • Mechanical Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.453" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits 					
Standard Features Plus:					
• Blower Housing to Accept Fixed Guard	27	CH740S	CH740-3012*	\$2,093.96	108
Standard Features Plus:					
• Blower Housing to Accept Fixed Guard	25	CH730	CH730-3208	\$1,679.81	108
• 3/16" Evaporative emissions connection	27	CH740	CH740-3006	\$2,060.76	108
	27	CH740	CH740-3009	\$2,092.95	108
Standard Features Plus:					
• Engine Controls-Key Switch, Throttle and Choke Controls	20	CH640	CH640-3007	\$1,674.33	106
	23	CH680	CH680-3002	\$1,719.60	106
• Fixed Grass Screen Guard (25 & 27 HP)	25	CH730	CH730-3203	\$1,959.74	108
• 3/16" Evaporative emissions connection	27	CH740	CH740-3005	\$2,121.66	108

*50-State Emission Version



18-27 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features Plus:					
• Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5"(38 mm) Deep, 7/16-20 UNF	18	CH620	CH620-3053	\$1,467.72	106
• Engine Controls-Key Switch, Throttle and Choke Controls	20	CH640	CH640-3008	\$1,674.33	106
	23	CH680	CH680-3001	\$1,677.75	106
• Fixed Grass Screen Guard (25 HP)	25	CH730	CH730-3201	\$1,924.93	108
• 3/16" Evaporative emissions connection	25	CH730	CH730-3209**	\$1,959.81	108
Standard Features Plus:					
• Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF					
• Engine Controls-Key Switch, Throttle and Choke Controls					
• Anti-Icing Features with Starter Side Exhaust System					
• Round Air Cleaner with Snorkel to Starter Side Muffler	20	CH640	CH640-3005	\$1,766.66	106
• Fixed Grass Screen Guard	25	CH730	CH730-3202	\$2,035.89	109
• 3/16" Evaporative emissions connection	27	CH740	CH740-3004	\$2,327.23	106
Standard Features Plus:					
• Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF					
• Engine Controls-Key Switch, Throttle and Choke Controls					
• Anti-Icing Features with Starter Side Exhaust System					
• Round Air Cleaner with Snorkel to Starter Side Muffler					
• Fixed Grass Screen Guard	27	CH740S	CH740-0071*	\$2,327.23	106
• PTO Thrust Bearing					

* Limited Quantity Available

** 50-State Emission Verison


18-27 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-2.25" (57.15 mm) Per Foot (305 mm) Taper, 1.5" (38 mm) Diameter x 3.94" (100.1 mm) PTO Length, Drilled and Tapped 0.625" (16 mm) Deep, 5/16-24 UNF • No PTO Thrust Bearing • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 6.437" (163 mm) Diameter Pilot • Oil Sentry™ Wired for Shutdown • Fixed Grass Screen Guard • Engine Controls-Key Switch and Choke Control • 5% Governor Regulation • Constant Speed @ 3200 RPM • 3/16" Evaporative emissions connection 					
	25	CH730	CH730-3210	\$2,327.23	108
Standard Features Plus:					
<ul style="list-style-type: none"> • Engine Mounted Throttle and Choke Controls • Key Switch Shipped as an Accessory • Fixed Grass Screen Guard • 25 Amp Alternator, Regulated • Crankshaft-1.5" (38 mm) Diameter x 0.452" (11.5 mm) PTO Length, 13 Tooth Spline, SAE "B" Mount Hydraulic Pump Adaptor • 3/16" Evaporative emissions connection 					
	25	CH730	CH730-3206	\$2,013.43	110
Standard Features Plus:					
Super Spec					
<ul style="list-style-type: none"> • 25 Amp Alternator • Dual Oil Fill • Clean Out Covers - Right Side Cover has Provision for Key Switch to be Added • 50 State Compliant • Provision for Adding Fixed Grass Screen Guard • To Add Controls Use These Parts: 24 225 02-S Throttle & Choke Assembly, 25 099 04-S Key Switch, Decals 24 113 126-S & 24 113 91-S • 3/16" Evaporative emissions connection 					
	25	CH730	CH730-3207	\$1,863.93	108

KOHLER Command PRO®

25 & 27 HP (Horizontal Shaft) V-Twin


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Heavy Duty Canister Air Cleaner System • Fixed Grass Screen Guard • Digital Spark Advance System (27 HP) • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Electronic Ignition • High Efficiency Grass Screen and Fan • Closed Breather System • Stellite® Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Large Capacity Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Variable Speed Governor • High Performance Accelerator Pump Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits • Standard Features Like CH740-0060 Plus EVAP 					
	27	CH740	CH740-3007	\$2,110.75	108
Standard Features Plus:					
• Engine Controls-Key Switch, Throttle and Choke Controls	25	CH730	CH730-3200	\$1,982.58	108
	27	CH740	CH740-3002	\$2,179.50	108
• 3/16" Evaporative emissions connection	27	CH740	CH740-3101	\$2,214.32	108
Standard Features Plus:					
• Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF					
• Engine Controls-Key Switch, Throttle and Choke Controls	25	CH730	CH730-3205	\$1,982.58	108
• 3/16" Evaporative emissions connection	27	CH740	CH740-3003	\$2,179.50	108



Heavy Duty Air Cleaner System

KOHLER Command PRO®


30 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Digital Spark Advance System • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Electronic Ignition • Large Capacity Dual Element Air Cleaner • High Efficiency Grass Screen and Fan • Closed Breather System • Stellite® Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Large Capacity Oil Filter, Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Variable Speed Governor • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • Crankshaft-1.437" (36 mm) Diameter x 4.453" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits 					
					
Standard Features Plus: <ul style="list-style-type: none"> • Fixed Grass Screen Guard • 25 Amp Alternator, Regulated • 3/16" Evaporative emissions connection 					
	30	CH750	CH750-3006	\$2,118.91	108
Standard Features Plus: <ul style="list-style-type: none"> • Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • Engine Controls-Key Switch, Throttle and Choke Controls • Fixed Grass Screen Guard • 25 Amp Alternator, Regulated • 3/16" Evaporative emissions connection 					
	30	CH750	CH750-3005	\$2,182.02	108

KOHLER Command PRO®


30 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Digital Spark Advance System • Heavy Duty Canister Air Cleaner System • Fixed Grass Screen Guard • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Electronic Ignition • High Efficiency Grass Screen and Fan • Closed Breather System • Stellite® Exhaust Valves • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Large Capacity Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Variable Speed Governor • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits • 3/16" Evaporative emissions connection 					
	30	CH750	CH750-3009	\$2,171.50	108
Standard Features Plus:					
<ul style="list-style-type: none"> • Engine Controls-Key Switch, Throttle and Choke Controls • Kohler HDAC • 3/16" Evaporative emissions connection 					
	30	CH750	CH750-3000	\$2,234.60	108
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • Engine Controls-Key Switch, Throttle and Choke Controls • Kohler HDAC • 3/16" Evaporative emissions connection 					
	30	CH750	CH750-3007	\$2,234.60	108




KOHLER Command PRO®

34, 36, 38, & 40 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Nylon Cam Gear • Cast-Iron Cylinder Liners • Stellite® Exhaust Valves • Flywheel and PTO Sleeve Bearings • Electronic Ignition • High Performance Spark Plugs RFI and EMC Compliant • Full Pressure Lubrication • Top Mount Spin-On Large Capacity Oil Filter • Large Dual Oil Drains • Heavy Duty Canister Air Cleaner System • High Efficiency Grass Screen and Fan • Fixed Grass Screen Guard • Blower Housing with Removable Cylinder Access Covers • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Oil Sentry™ (Switch Installed but Unconnected) • Variable Speed Governor • Front Mounted Remote Controls (for boden wire connection) • Closed Breather System • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • Large Capacity In-Line Fuel Filter • 12 Volt Solenoid Shift Starter • 25 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum 					
					
Standard Features Plus:					
• 3/16" Evaporative emissions connection	34	CH940	CH940-2002	\$2,378.56	132
	36	CH960	CH960-2002	\$2,552.48	132
	38	CH980	CH980-2002	\$2,769.90	132
	40	CH1000	CH1000-2002	\$3,074.27	132
Standard Features Plus:					
• Crankshaft-1.125" (28.5 mm) Diameter x 3.35" (85 mm) PTO Length	34	CH940	CH940-2003	\$2,418.73	132
	36	CH960	CH960-2003	\$2,592.67	132
• 3/16" Evaporative emissions connection	38	CH980	CH980-2003	\$2,810.07	132

KOHLER Command PRO®

34, 38, & 40 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Nylon Cam Gear • Cast-Iron Cylinder Liners • Stellite® Exhaust Valves • Flywheel and PTO Sleeve Bearings • Electronic Ignition • High Performance Spark Plugs RFI and EMC Compliant • Full Pressure Lubrication • Top Mount Spin-On Large Capacity Oil Filter • Large Dual Oil Drains • Flat Air Cleaner • High Efficiency Grass Screen and Fan • Fixed Grass Screen Guard • Blower Housing with Removable Cylinder Access Covers • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Oil Sentry™ (Switch Installed but Unconnected) • Variable Speed Governor • Front Mounted Remote Controls (for boden wire connection) • Closed Breather System • Two-Barrel Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • Large Capacity In-Line Fuel Filter • 12 Volt Solenoid Shift Starter • 25 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum 					
					
Standard Features Plus:					
• 3/16" Evaporative emissions connection	34	CH940	CH940-2005	\$2,366.38	132
	38	CH980	CH980-2005	\$2,757.71	132
Standard Features Plus:					
Mud Boat Spec					
• Crankshaft-1.125" (28.5 mm) Diameter x 4.00" (101.6 mm) PTO Length					
• Remote Throttle Manual Choke (Engine Mounted Key Switch					
• Canister Muffler PTO Outlet (62 786 01-S Installed)					
• 3/16" Evaporative emissions connection	40	CH1000	CH1000-2012	\$3,117.59	132

Control Kit and Exhaust System Kits

Kit/Part No.	Description	List Price
62 376 02-S	Engine Mounted Control Kit (Includes Key Switch, Panel, Oil Sentry Light, Decal Knobs, Brackets, and Screws)	\$75.68
62 786 01-S	PTO Canister Muffler Kit-Center Outlet (Includes Muffler)	\$121.05
62 786 02-S	PTO Canister Muffler Kit-Starter Side Outlet (Includes Muffler).....	\$121.05
62 786 03-S	PTO Canister Muffler Kit-Opposite Starter Side Outlet (Includes Muffler)	\$121.05


KOHLER Command PRO. EFI

27 & 29 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
-------------	----	-------	-----------	------------	------------------------

Standard Features:

- Overhead Valve Design
- Hydraulic Valve Lifters
- Cast-Iron Cylinder Liners
- PTO Sleeve Bearing (Side Load)
- Electronic Ignition
- Heavy Duty Canister Air Cleaner System (Kohler)
- High Efficiency Grass Screen and Fan
- Closed Breather System
- Stellite® Exhaust Valves
- Full Pressure Lubrication
- In-Line Fuel Filter
- Easy Access Valve Cover Oil Fill-Yellow
- Oil Level Dipstick-Yellow
- Large Capacity Oil Filter, Dual Oil Drain
- Oil Sentry™
- Variable Speed Governor
- Mechanical Fuel Pump
- High Performance Spark Plugs
- 12 Volt Solenoid Shift Starter
- Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF
- PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep
- 7" (178 mm) Diameter Pilot
- Color-Black with Cast Aluminum
- Engine Controls-Key Switch and Throttle Control
- Fixed Grass Screen Guard
- 20 Amp Alternator, Regulated
- 3/16" Evaporative emissions connection
- See page 37 for Exhaust System Kits



27	ECH740	ECH740-3002	\$2,421.10	108
29	ECH749	ECH749-3002	\$2,474.13	108

Standard Features Plus:


- Crankshaft-1.437" (36.5 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF

27	ECH740	ECH740-3001	\$2,421.10	108
29	ECH749	ECH749-3003	\$2,474.13	108

KOHLER Command PRO[®] EFI

19, 21, 25, 27 & 29 HP (Horizontal Shaft) V-Twin


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Electronic Ignition • Large Capacity Dual Element Air Cleaner • High Efficiency Grass Screen and Fan • Closed Breather System • Stellite[®] Exhaust Valves • Full Pressure Lubrication • In-Line Fuel Filter • Easy Access Valve Cover Oil Fill-Yellow • Oil Level Dipstick-Yellow • Large Capacity Oil Filter, Dual Oil Drain • Oil Sentry[™] • Variable Speed Governor • Mechanical Fuel Pump • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • Fixed Grass Screen Guard • 20 Amp Alternator, Regulated • 3/16" Evaporative emissions connection • See page 37 for Exhaust System Kits 					
	19	ECH630	ECH630-3003	\$1,624.05	108
	25	ECH730	ECH730-3003	\$2,061.92	108
Standard Features Plus: <ul style="list-style-type: none"> • Crankshaft-1.437" (36.5 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • Engine Controls-Key Switch and Throttle Control 					
	21	ECH650	ECH650-3002	\$1,872.58	108
	25	ECH730	ECH730-3001	\$2,110.70	108
	27	ECH740	ECH740-3003	\$2,364.62	108
Standard Features Plus: <ul style="list-style-type: none"> • 25 Amp Alternator, Regulated 					
	29	ECH749	ECH749-3004	\$2,374.00	108
Standard Features Plus: <ul style="list-style-type: none"> • 25 Amp Alternator, Regulated • Engine Controls-Key Switch and Throttle Control 					
	29	ECH749	ECH749-3001	\$2,422.78	108



KOHLER Command®

18 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Electronic Ignition • Dual Element Air Cleaner • Closed Breather System • Stellite® Exhaust Valves • Cast Iron Cylinder Liners • Full Pressure Lubrication • In-Line Fuel Filter • Easy Access Valve Cover Oil Fill • Oil Level Dipstick • Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Variable Speed Governor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • 12 Volt Solenoid Shift Starter • 15 Amp Alternator, Regulated • Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits/Parts 					
Standard Features Plus:					
• 3/16" Evaporative emissions connection	18	CH620	CH620-3002	\$1,379.01	106
Standard Features Plus:					
• Engine Controls-Key Switch, Throttle and Choke Controls (Pro version 62587)					
• 3/16" Evaporative emissions connection	18	CH620	CH620-3003	\$1,413.27	106
Standard Features Plus:					
• Engine Controls-Key Switch, Throttle and Choke Controls					
• Crankshaft-1" (25.4 mm) Diameter x 3.0" (76 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1" (25.4 mm) Deep, 3/8-24 UNF					
• PTO Face-5" (127 mm) Diameter, (4 Holes) 5/16-24 x 0.67" (17 mm) Deep, 6.5" (165 mm) Diameter, (4 Holes), 3/8-16, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep					
• 5.75" (146 mm) Diameter Pilot					
• 3/16" Evaporative emissions connection	18	CH620	CH620-3004	\$1,413.27	106



18 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-1" (25.4 mm) Diameter x 3.0" (76 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1" (25.4 mm) Deep, 3/8-24 UNF • PTO Face-5" (127 mm) Diameter, (4 Holes) 5/16-24 x 0.67" (17 mm) Deep, 6.5" (165 mm) Diameter, (4 Holes) 3/8-16 x 0.83" (21 mm) Deep, 7.75" (197 mm) Diameter (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 5.75" (146 mm) Diameter Pilot • 3/16" Evaporative emissions connection 					
	18	CH620	CH620-3005	\$1,379.00	106
Standard Features Plus:					
<ul style="list-style-type: none"> • Engine Controls-Key Switch, Throttle and Choke Controls • Anti-Icing Features with Starter Side Exhaust System • Fixed Grass Screen Guard • Round Air Cleaner with Snorkel to Starter Side Muffler • 3/16" Evaporative emissions connection 					
	18	CH620	CH620-3006	\$1,557.38	106
Standard Features Plus:					
<ul style="list-style-type: none"> • Crankshaft-2.25" (57.15 mm) Per Foot (305 mm) Taper, 1.5" (38 mm) Diameter x 3.94" (100.1 mm) PTO Length, Drilled and Tapped 0.625" (16 mm) Deep, 5/16-24 UNF • PTO Face-5.625" (143 mm) Diameter (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 6.437" (163 mm) Diameter Pilot • Oil Sentry™ Wired for Shutdown • Fixed Grass Screen Guard • Engine Controls-Key Switch and Choke Control • 5% Governor Regulation • Constant Speed @ 3200 RPM • 3/16" Evaporative emissions connection 					
	18	CH620	CH620-3007	\$1,497.62	107
Standard Features Plus:					
<ul style="list-style-type: none"> • 9 Tooth Spline Crankshaft • Engine Controls-Key Switch, Throttle and Choke Controls (Pro version 62587) • SAE "A" Mount Hydraulic Pump Adapter • 3/16" Evaporative emissions connection 					
	18	CH620	CH620-3008	\$1,497.62	106

18 HP (Horizontal Shaft) V-Twin


Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features Plus:					
<ul style="list-style-type: none"> • Engine Controls-Key Switch, Throttle and Choke Controls • Retractable Start Backup • Crankshaft-1" (25.4 mm) Diameter x 3.0" (76.2 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1" (25.4 mm) Deep, 3/8-24 UNF • PTO Face-5" (127 mm) Diameter, (4 Holes) 5/16-24 x 0.67" (17 mm) Deep, 6.5" (165 mm) Diameter, (4 Holes) 3/8-16 x 0.83" (21 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 5.75" (146 mm) Diameter Pilot • 3/16" Evaporative emissions connection 					
	18	CH620	CH620-3009	\$1,463.23	106

Aegis and Command Exhaust System Kits/Parts

Kit/Part No.	Description	List Price (each)
24 786 04-S	PTO Canister Muffler Kit-Center Outlet (CH18-22).....	\$105.81
24 786 05-S	PTO Canister Muffler Kit-Filter Side Outlet (CH18-22)	\$105.81
24 786 06-S	PTO Canister Muffler Kit-Starter Side Outlet (CH18-22)	\$105.81
24 786 08-S	Side Mount Muffler Kit-Starter Side (CH18-22).....	\$180.59
24 786 09-S	Side Mount Muffler Kit-Filter Side (CH18-22)	\$180.59
24 786 10-S	PTO Canister Muffler Kit-Center Outlet (CH25/CH730/CH740, LH640-755)	\$136.57
24 786 11-S	PTO Canister Muffler Kit-Filter Side Outlet (CH25/CH730/CH740, LH640-755)	\$136.57
24 786 12-S	PTO Canister Muffler Kit-Starter Side Outlet (CH25/CH730/CH740, LH640-755)	\$130.07
24 786 13-S	Valve Cover Mounting Muffler Kit-Starter Side (for "00" spec. variation) (CV18-22) .	\$197.76
24 786 14-S	Valve Cover Mounting Muffler Kit-Filter Side (for "00" spec. variation) (CV18-22)....	\$193.80
24 786 19-S	Side Mount Muffler Kit-Starter Side (CH25/CH730/CH740, LH640-755)	\$223.59
24 786 20-S	Side Mount Muffler Kit-Filter Side (CH25/CH730/CH740, LH640-755)	\$248.08
24 786 21-S	Raised Body PTO Canister Kit-Filter Side Outlet (CH18-740, LH640-755).....	\$161.41
24 786 22-S	Raised Body PTO Canister Kit-Starter Side Outlet (CH18-740, LH640-755).....	\$161.41
25 755 36-S	Mounting Kit, Canister Muffler (CH745, LH775)	\$30.50
24 786 24-S	Side Mount Muffler Kit - Starter Side (CH745, LH775)	\$177.75
24 786 25-S	Side Mount Muffler Kit - Filter Side (CH745, LH775)	\$177.75
24 786 28-S	Muffler Kit – Starter Side (Command EFI Verticals).....	\$155.84
24 786 29-S	Muffler Kit – Filter Side (Command EFI Verticals).....	\$155.84
24 786 30-S	Muffler Kit – Filter Side Down (Command EFI Verticals).....	\$209.87
24 786 31-S	Muffler Kit – Starter Side (Command EFI Horizontals).....	\$123.66
24 786 32-S	Muffler Kit – Filter Side (Command EFI Horizontals).....	\$123.71
24 786 33-S	Muffler Kit – Center Outlet (Command EFI Horizontals).....	\$122.72


KOHLER Command.

20 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Overhead Valve Design • Hydraulic Valve Lifters • Electronic Ignition • Dual Element Air Cleaner • Closed Breather System • Stellite® Exhaust Valves • Cast Iron Cylinder Liners • Full Pressure Lubrication • In-Line Fuel Filter • Easy Access Valve Cover Oil Fill • Oil Level Dipstick • Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Variable Speed Governor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump • 12 Volt Solenoid Shift Starter • 15 Amp Alternator, Regulated • Crankshaft-1.437" (36 mm) Diameter x 4.41" PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum • See page 37 for Exhaust System Kits/Parts 					
					
Standard Features Plus: <ul style="list-style-type: none"> • Standard Features Like 64500 Plus 3/16" Evaporative emissions connection 					
	20	CH640	CH640-3006	\$1,582.63	106
Standard Features Plus: <ul style="list-style-type: none"> • Engine Controls-Key Switch, Throttle and Choke Controls (Pro version 64594) 					
• 3/16" Evaporative emissions connection	20	CH640	CH640-3002	\$1,617.83	106
Standard Features Plus: <ul style="list-style-type: none"> • Engine Controls-Key Switch, Throttle and Choke Controls • Crankshaft-1.125" (28.5 mm) Diameter x 4.0" (102 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF (Pro version 64595) 					
• 3/16" Evaporative emissions connection	20	CH640	CH640-3004	\$1,617.83	106

24-31 HP (Horizontal Shaft) V-Twin

Description	HP	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:					
<ul style="list-style-type: none"> • Liquid-Cooled with High Efficiency Radiator • Overhead Valve Design • Hydraulic Valve Lifters • Electronic Ignition • Cast-Iron Cylinder Liners • PTO Sleeve Bearing (Side Load) • Heavy Duty, Dual Element Commercial Air Cleaner • Closed Breather System • Debris Screen • Stellite® Exhaust Valves, with Seat Inserts • Full Pressure Lubrication • Large Capacity In-Line Fuel Filter • Easy Access Oil Fill and Dipstick Location-Yellow • Large Capacity Oil Filter • Dual Oil Drain • Oil Sentry™ (Switch Installed and Wired but Unconnected) • Accepts Command Twin PTO Mount Muffler • High Mount Controls for Boden Wires • Variable Speed Governor • High Performance Accelerator Pump Carburetor • Fuel Shutdown Solenoid • Smart-Choke™ Carburetor • Mechanical Fuel Pump (Oil Filter Side Valve Cover) • High Performance Spark Plugs • 12 Volt Solenoid Shift Starter • 20 Amp Alternator, Regulated • Crankshaft-1.437" (36.5 mm) Diameter x 4.46" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF • PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-4 x 0.83" (21 mm) Deep • 7" (178 mm) Diameter Pilot • Color-Black with Cast Aluminum 					
	24	LH640S	LH640-3001	\$2,327.11	125
• See page 37 For Exhaust System Kits/Parts	26	LH690S	LH690-3001	\$2,409.28	125
31 HP Electronic Fuel Injection (EFI) Model:					
<ul style="list-style-type: none"> • Standard Features Like LH755-0001 Plus: • Complete EFI System Less Muffler 					
	31	LH775S	LH775-0001	\$2,845.14	130



KOHLER[®]Diesel

KD350 (Single Cylinder) 6.7 HP (5 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • 1" Diameter Integral Keyed Shaft (Ext 4) • Internal Oil Filter • Dry Type Air Cleaner • Inline Fuel Filter • 4.3 L Fuel Tank • Muffler w/Guard • 3600 rpm • SAE J609a Flanges A/B • Manual Throttle and Stop Controls • Tier 4 compliant (Hand start provision) • Recoil Start 				
				
	KD350	KD350-1001	\$1,732.79	120
Standard Features Plus: <ul style="list-style-type: none"> • 12 Volt Electric Start • Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • 12A Alternator 				
	KD350	KD350-2001	\$2,086.40	120
Standard Features Plus: <ul style="list-style-type: none"> • Generator Crankshaft (Ext 6 long taper) 				
	KD350	KD350-3001	\$1,776.54	120
Standard Features Plus: <ul style="list-style-type: none"> • 12 Volt Electric Start • Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • 12A Alternator 				
	KD350	KD350-4001	\$2,088.35	120
Standard Features Plus: <ul style="list-style-type: none"> • 5/8" Threaded Crankshaft (Ext 7) 				
	KD350	KD350-5001	\$1,776.54	120
Standard Features Plus: <ul style="list-style-type: none"> • 12 Volt Electric Start • Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • 12A Alternator 				
	KD350	KD350-6001	\$2,088.35	120
Standard Features Plus: <ul style="list-style-type: none"> • 3/4" Crankshaft (Ext 3) 				
	KD350	KD350-7001	\$1,776.54	120
Standard Features Plus: <ul style="list-style-type: none"> • 12 Volt Electric Start • 12A Alternator • Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure 				
	KD350	KD350-8002	\$2,088.35	120

Note: Orders will be filled with old spec number until stock is depleted.

KOHLER[®]Diesel

KD420 (Single Cylinder) 9.8 HP (7.3 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:				
<ul style="list-style-type: none"> • 1" Diameter Integral Keyed Shaft (Ext 4) • Counter Balance Shaft • Internal Oil Filter • Dry Type Air Cleaner • Inline Fuel Filter • 5 L Fuel Tank • Muffler w/Guard • 3600 rpm • SAE J609a Flange B • Manual Throttle and Stop Controls • EGR (Exhaust Gas Recirculation) • Tier 4 compliant (Hand start provision) • Recoil Start 				
	KD420	KD420-1001	\$1,984.39	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 20 Amp Alternator, Control Panel • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure 				
	KD420	KD420-2001	\$2,413.07	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 20 Amp Alternator • Control panel with auto glow plug timer • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • Glow plugs (cold start aid) 				
	KD420	KD420-2101	\$2,502.40	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 1" Threaded Crankshaft (Ext 9) 				
	KD420	KD420-3001	\$2,037.15	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 12A Alternator, Control Panel with Integral Voltage Regulator • Manual shut down • 1" Threaded Crankshaft (Ext 9) 				
Less: Safety Shutdown for Low Oil Pressure	KD420	KD420-4001	\$2,407.88	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 12A Alternator, Control Panel with Integral Voltage Regulator • Manual shut down • Conical Crankshaft (short taper) 				
Less: Safety Shutdown for Low Oil Pressure	KD420	KD420-5001	\$2,199.39	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 12A Alternator, Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • Generator Crankshaft (Ext 6 long taper) • Fuel Lift Pump 				
Less: fuel tank	KD420	KD420-6001	\$2,466.37	125



KD420 (Single Cylinder) 9.8 HP (7.3 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 12A Alternator, Control Panel with Integral Voltage Regulator • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • Generator Crankshaft (Ext 6 long taper) • Fuel Lift Pump • Glow plugs (cold start aid) 				
Less: fuel tank	KD420	KD420-6101	\$2,552.07	125
Standard Features Plus:				
<ul style="list-style-type: none"> • 12 Volt Electric Start • 20 Amp Alternator, Control Panel • Electronic Shutdown Fuel Valve • Safety Shutdown for Low Oil Pressure • Fuel Lift Pump 				
Less: fuel tank	KD420	KD420-7002	\$2,426.18	125

KOHLER.Diesel

KD425-2 (Twin Cylinder) 18.8 HP (14 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • 12 Volt Starter with 16 Amp Alternator • Electric Control Panel • Glow Plugs (Cold Start Aid) • Low Oil Pressure Safety Shutdown • Electronic Shutdown Fuel Valve • Lube Oil Filter with Cooler • Dry Type Air Cleaner • Fuel Filter • Standard Mounting Feet • Muffler with Guard • Throttle & Stop Control Lever • 3600 rpm 				
Standard Features Plus: Standard Industrial Spec • 1-1/8" Keyed Shaft w 7.0" Flange				
	KD425-2	KD4252-1001	\$4,232.21	117
Standard Features Plus: Standard Industrial Spec • 1-1/8" Keyed Shaft w 7.0" Flange Less: Exhaust Manifold Less: Exhaust Muffler				
	KD425-2	KD4252-1101	\$4,180.16	117
Standard Features Plus: Generator Spec • SAE J609 Type B Metric Adapter				
	KD425-2	KD4252-2001	\$4,225.49	117
Standard Features Plus: Hydraulic Spec • Hydraulic Flange & Pump Drive SAE 2A-9T				
	KD425-2	KD4252-3001	\$4,484.72	117




KOHLER[®]Diesel

KD477-2 (Twin Cylinder) 17.2 HP (12.8 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • 12 Volt Starter with 18 Amp Alternator • Deluxe Electric Control Panel • Glow Plugs (Cold Start Aid) • Safety Shutdown for Low Oil Pressure • Electronic Shutdown Fuel Valve • Oil Filter • Muffler with Guard • Oil Bath Air Cleaner w Pre-cleaner • Fuel Filter • Throttle & Stop Control Lever • Standard Mounting Feet • 2700 rpm 				
				
Standard Features Plus:				
Standard Industrial Spec				
• 1-1/8" Keyed Shaft w 7.0" Flange	KD477-2	KD4772-1001	\$4,277.82	245
Standard Features Plus:				
Hydraulic Pump Spec				
• SAE 2A-9T (Installed)	KD477-2	KD4772-2001	\$4,443.18	245
Standard Features Plus:				
Standard Industrial Spec				
• SAE 5 housing and 6 1/2" flywheel	KD477-2	KD4772-3001	\$4,284.64	245


KOHLER[®] Diesel

KD625-2 (Twin Cylinder) 25.2 HP (18.8 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • 12 Volt Starter with 18 Amp Alternator • Electric Control Panel • Oil Bath Air Cleaner w/Pre-cleaner • Manifold Horizontal Muffler • Lube Oil Filter • Fuel Filter • Electronic Shutdown Fuel Valve • Manual Throttle & Stop Lever Control • Group 8 housing & flywheel • Fuel Lift Pump • Standard Engine Mounting Feet • 3000 rpm 				
				
	KD625-2	KD6252-1001	\$4,521.63	290
Standard Features Plus: <ul style="list-style-type: none"> • Dry type HD air cleaner canister (loose) • Intake manifold with A/C hose adapter 				
Less: Exhaust Manifold				
Less: Exhaust Muffler	KD625-2	KD6252-1101	\$4,460.91	290
Standard Features Plus: <ul style="list-style-type: none"> • With 10 L Fuel Tank • 14 A Alternator 				
Less: Electronic Shutdown Fuel Valve	KD625-2	KD6252-2001	\$4,685.69	290


KOHLER[®] Diesel

KDW702 (Twin Cylinder) 16.8 HP (12.5 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Mounted Top Tank Radiator • Radiator Fan Guard • Mounted Air Cleaner • Muffler • Muffler Guard • 12 Volt Electric Starter Motor with 45 Amp External Alternator • Glow Plugs • Fuel Filter • Electronic Shutdown Fuel Valve • Mounting Feet • Mounted Control Panel • Safety shutdown for low oil pressure, high coolant temp, and alternator charge 				
				
Standard Features Plus:				
<ul style="list-style-type: none"> • High Speed 3600 RPM • Puller Fan • Group 8 housing and flywheel 	KDW702	KDW702-1001	\$4,401.90	260
Standard Features Plus:				
<ul style="list-style-type: none"> • 7 mm back plate 	KDW702	KDW702-1101	\$4,295.43	235
Standard Features Plus:				
<ul style="list-style-type: none"> • Low Speed 1800 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW702	KDW702-2001	\$4,442.26	260
Standard Features Plus:				
<ul style="list-style-type: none"> • Gen Speed 3600 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW702	KDW702-4001	\$4,442.26	260
Standard Features Plus:				
<ul style="list-style-type: none"> • Fan to Flywheel High Speed 3600 RPM • Puller Fan • 12 Volt Electric Starter Motor with 45 Amp external Alternator • Manual Shutdown • 7 mm back plate • Canister Air Cleaner (loose) • less radiator • less Muffler • less Control Panel 	KDW702	KDW702-1201	\$4,083.23	150


KOHLER Diesel

KDW1003 (3 Cylinder) 26.1 HP (19.5 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Mounted Top Tank Radiator • Radiator Fan Guard • Mounted Air Cleaner • Muffler • Muffler Guard • 12 Volt Electric Starter Motor with 45 Amp External Alternator • Glow Plugs • Fuel Filter • Electronic Shutdown Fuel Valve • Mounting Feet • Mounted Control Panel • Safety shutdown for low oil pressure, high coolant temp, and alternator charge 				
				
Standard Features Plus:				
<ul style="list-style-type: none"> • High Speed 3600 RPM • Puller Fan • Group 8 housing and flywheel 	KDW1003	KDW1003-1001	\$4,704.98	320
Standard Features Plus:				
<ul style="list-style-type: none"> • 7 mm back plate 	KDW1003	KDW1003-1101	\$4,595.68	295
Standard Features Plus:				
<ul style="list-style-type: none"> • Low Speed 1800 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW1003	KDW1003-2001	\$4,704.98	320
Standard Features Plus:				
<ul style="list-style-type: none"> • Gen Speed 3600 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW1003	KDW1003-3001	\$4,704.98	320
Standard Features Plus:				
<ul style="list-style-type: none"> • Fan to Flywheel High Speed 3600 RPM • Puller Fan • 12 Volt Electric Starter Motor with 45 Amp external Alternator • Manual Shutdown • 7 mm back plate • Canister Air Cleaner (loose) • less radiator • less Muffler • less Control Panel 	KDW1003	KDW1003-1201	\$4,339.65	190

KOHLER[®] Diesel

KDW1404 (4 Cylinder) 34.9 HP (26 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Mounted Top Tank Radiator • Radiator Fan Guard • Mounted Air Cleaner • Muffler • Muffler Guard • 12 Volt Electric Starter Motor with 45 Amp External Alternator • Glow Plugs • Fuel Filter • Electronic Shutdown Fuel Valve • Mounting Feet • Mounted Control Panel • Safety shutdown for low oil pressure, high coolant temp, and alternator charge 				
				
Standard Features Plus:				
<ul style="list-style-type: none"> • High Speed 3600 RPM • Puller Fan • Group 8 housing and flywheel 	KDW1404	KDW1404-1001	\$5,802.83	350
Standard Features Plus:				
<ul style="list-style-type: none"> • Low Speed 1800 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW1404	KDW1404-2001	\$5,802.83	350
Standard Features Plus:				
<ul style="list-style-type: none"> • Gen Speed 3600 RPM • Pusher Fan • SAE 5 housing and 6 ½" flywheel 	KDW1404	KDW1404-3001	\$5,507.09	350

KOHLER[®]Diesel

KDW1603 (3 Cylinder) 40.2 HP (30 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:				
<ul style="list-style-type: none"> • Mounted Top Tank Radiator <ul style="list-style-type: none"> • Radiator Fan Guard • Mounted Air Cleaner • Muffler • Muffler Guard • 12 Volt Electric Starter Motor with 45 Amp External Alternator • Glow Plugs • Fuel Filter • Electronic Shutdown Fuel Valve • Mounting Feet • Mounted Control Panel • Safety shutdown for low oil pressure, high coolant temp, and alternator charge 				
Standard Features Plus:				
<ul style="list-style-type: none"> • High Speed 3000 RPM • Puller Fan • Group 5 housing and flywheel 	KDW1603	KDW1603-1001	\$6,082.02	488
Standard Features Plus:				
<ul style="list-style-type: none"> • Low Speed 1800 RPM • Pusher Fan • SAE 5 housing and 7 ½" flywheel 	KDW1603	KDW1603-2001	\$6,213.12	488



KOHLER[®]Diesel


KDW2204 (4 Cylinder) 51 HP (38 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features: <ul style="list-style-type: none"> • Mounted Top Tank Radiator • Radiator Fan Guard • Mounted Air Cleaner • Muffler • Muffler Guard • 12 Volt Electric Starter Motor with 45 Amp External Alternator • Glow Plugs • Fuel Filter • Electronic Shutdown Fuel Valve • Mounting Feet • Mounted Control Panel • Safety shutdown for low oil pressure, high coolant temp, and alternator charge 				
Standard Features Plus: <ul style="list-style-type: none"> • High Speed 3000 RPM • Puller Fan • Group 5 housing and flywheel 				
	KDW2204	KDW2204-1001	\$7,306.87	550
Standard Features Plus: <ul style="list-style-type: none"> • Low Speed 1800 RPM • Pusher Fan • SAE 5 housing and 7 ½" flywheel 				
	KDW2204	KDW2204-2001	\$7,464.37	550



KOHLER[®]Diesel

KDW2204T (4 Cylinder) 64.4 HP (48 kW)

Description	Model	Spec. No.	List Price	Approx. Ship Wt. (lb.)
Standard Features:				
<ul style="list-style-type: none">• Turbo charged• Mounted Top Tank Radiator• Radiator Fan Guard• Mounted Air Cleaner• Muffler• Muffler Guard• 12 Volt Electric Starter Motor with 45 Amp External Alternator• Glow Plugs• Fuel Filter• Electronic Shutdown Fuel Valve• Mounting Feet• Mounted Control Panel• Safety shutdown for low oil pressure, high coolant temp, and alternator charge				
				
Standard Features Plus:				
<ul style="list-style-type: none">• Low Speed 1800 RPM• Pusher Fan• SAE 5 housing and 7 ½" flywheel				
	KDW2204T	KDW2204T-2001	\$8,292.39	576

EVAP Cross Reference
Courage and Command Basic Engines

Model	HP	Old Spec No.	EVAP Spec No.
CH18	18	62500	CH620-3002
CH18	18	62501	CH620-3003
CH18	18	62502	CH620-3005
CH18	18	62503	CH620-3004
CH18	18	62504	CH620-3007
CH18	18	62505	CH620-3009
CH18	18	62506	CH620-3008
CH18	18	62507	CH620-3006
CH18	18	62587	CH620-3053
CH20	20	64500	CH640-3006
CH20	20	64501	CH640-3002
CH20	20	64503	CH640-3004
CH20	20	64594	CH640-3007
CH20	20	64595	CH640-3008
CH20	20	64672	CH640-3005
CH23	23	76501	CH680-3002
CH23	23	76601	CH680-3001
CH730	25	CH730-0001	CH730-3200
CH730	25	CH730-0002	CH730-3205
CH730	25	CH730-0038	CH730-3038
CH730	25	CH730-0039	CH730-3201
CH730	25	CH730-0040	CH730-3203
CH730	25	CH730-0041	CH730-3202
CH730	25	CH730-0108	CH730-3210
CH730	25	CH730-3038	CH730-3208
CH730	25	CH730-3039	CH730-3209
CH730	25	CH730-3040	CH730-3203
CH730	25	CH730-3131	CH730-3206
CH730	25	CH730-3217	CH730-3207
CH740	27	CH740-0001	CH740-3002
CH740	27	CH740-0002	CH740-3003
CH740	27	CH740-0004	CH740-3004
CH740	27	CH740-0012	CH740-3006
CH740	27	CH740-0013	CH740-3005
CH740	27	CH740-0060	CH740-3007
CH740	27	CH740-3001	CH740-3101
CH740	27	CH740-3012	CH740-3009
CH740	27	CH740-3135	CH740-3008
CH745	28	CH745-0010	CH745-3100
CH750	30	CH750-0005	CH750-3005
CH750	30	CH750-0006	CH750-3006
CH750	30	CH750-0007	CH750-3007
CH750	30	CH750-0008	CH750-3000
CH750	30	CH750-0009	CH750-3009

EVAP Cross Reference
Courage and Command Basic Engines

Model	HP	Old Spec No.	EVAP Spec No.
CH940	34	CH940-0002	CH940-2002
CH940	34	CH940-0003	CH940-2003
CH940	34	CH940-0005	CH940-2005
CH960	36	CH960-0002	CH960-2002
CH960	36	CH960-0003	CH960-2003
CH980	38	CH980-0002	CH980-2002
CH980	38	CH980-0003	CH980-2003
CH980	38	CH980-0005	CH980-2005
CH1000	40	CH1000-0002	CH1000-2002
CH1000	40	CH1000-0012	CH1000-2012
CV18	18	61500	CV620-3001
CV20	20	65500	CV640-3001
CV23	23	75500	CV680-3001
CV23	23	75550	CV680-3002
CV730	25	CV730-0001	CV730-3101
CV740	27	CV740-0001	CV740-3001
CV750	30	CV750-0005	CV750-3005
CV940	34	CV940-0002	CV940-2002
CV960	36	CV960-0002	CV960-2002
CV980	38	CV980-0002	CV980-2002
SV480	16	SV480-0200	SV480-3200
SV540	18	SV540-0202	SV540-3202
SV600	20	SV600-0202	SV600-3202
SV610	21	SV610-0200	SV610-3200
SV620	22	SV620-0202	SV620-3202
SV725	24	SV725-0002	SV725-3002
SV735	26	SV735-0002	SV735-3002

KOHLER[®] ENGINES

FOR SALES AND SERVICE INFORMATION
IN U.S. AND CANADA, CALL **1-800-544-2444**

KohlerEngines.com

ENGINE DIVISION, KOHLER CO., KOHLER, WISCONSIN 53044

© 2011 by Kohler Co. All rights reserved.

FORM NO.:	TP-2389-T
ISSUED:	09/11
REVISED:	



1PTP-2389-T



6 50531 91706 5