



## MURRAY SNOWTHROWERS



Briggs & Stratton Snow Series engines are designed to run in the toughest cold weather conditions. The overhead valve (OHV) engines provide quiet, smooth operations, better fuel efficiency and reduced emissions. They are equipped with electric start and synthetic oil for easier starting.



**MURRAY®**



# SNOWTHROWERS

## Model Specs



Duty Type	Electric Single Stage	Single Stage	Dual Stage	Dual Stage	Dual Stage	Dual Stage	Dual Stage	Dual Stage
Model Description	20" Electric	8.00 TP 22"	8.00 TP 24"	8.00 TP 24"	9.00 TP 27"	11.50 TP 27"	14.50 TP 29"	16.50 TP 33"
Briggs & Stratton Number	1695772*	1695885	1696047 1695978	1695979	1696028	1696029	1696030	1695838
Clearing width	20"	22"	24"	24"	27"	27"	29"	33"
Engine Model	NA	Briggs & Stratton 800 Snow Series™	Briggs & Stratton 800 Snow Series™	Briggs & Stratton 800 Snow Series™	Briggs & Stratton 900 Snow Series™	Briggs & Stratton 1150 Snow Series™	Briggs & Stratton 1450 Snow Series™	Briggs & Stratton 1650 Snow Series™
Ft-lbs Gross Torque**	NA	8.00 OHV	8.00 OHV	8.00 OHV	9.00 OHV	11.50 OHV	14.50 OHV	16.50 OHV
CC	NA	205	205	205	205	250	305	342
Starting System	12 Amp electric motor	110V Electric Start with recoil back up	110V Electric Start with recoil back up (non-electric start 1695978)	110V Electric Start with recoil back up	110V Electric Start with recoil back up	110V Electric Start with recoil back up	110V Electric Start with recoil back up	110V Electric Start with recoil back up
Auger Type	Rubber flighted	Rubber flighted	Steel notched	Steel notched	Steel notched	Steel notched	Steel notched	Steel notched
Intake Height	10.25"	12.5"	20"	20"	21"	21"	21"	23.5"
Drive Type	Auger propelled	Auger propelled	Friction Disc	Friction Disc	Friction Disc	Friction Disc	Friction Disc Easy Steer	Friction Disc Steerable
Speeds	NA	NA	3 FW/ 2 RV	6 FW/ 2 RV	6 FW/ 2 RV	6 FW/ 2 RV	6 FW/ 2 RV	6 FW/ 2 RV
Chute Rotation	Manual	200° Manual	200° Manual	Manual left side crank 190° (3.5 turn)	Manual left side crank 190° (3.5 turn)	Dash mounted crank 190° (3.5 turn)	Dash mounted crank 190° (3.5 turn)	Dash mounted crank 190° (3.5 turn)
Chute Deflector	Manual	Manual	Manual	Manual	Manual	Dash Mounted	Dash Mounted	Dash Mounted
Free Hand Control	NA	NA	NA	No	No	Yes	Yes	Yes
Tire Size	7" x 1.5"	8" x 2"	10" x 4"	13" x 5"	16" x 4.8"	16" x 4.8"	16" x 6.5"	16" x 6.5"
Headlight	NA	NA	NA	No	No	Yes	Yes	Yes
Heated Hand Grips	NA	NA	NA	No	No	No	Yes	Yes
Warranty	1 year limited	1 year limited	2 year limited	2 year limited	2 year limited	2 year limited	2 year limited	2 year limited

\* Available in Canada Only

\*\* All power levels stated ft-lbs gross torque per SAE J1940 by Briggs & Stratton

BRIGGS & STRATTON

POWER PRODUCTS GROUP, LLC  
MILWAUKEE, WI 53201 USA  
Copyright © 2011. All rights reserved.

