

iX800

iX SERIES
Commercial/Residential
Portable Generators

iX800

1 of 2

A/C Rated Output Watts: 800

A/C Maximum Output Watts: 850

Model 5791-0

UPC Number: 696471057911

Emissions Certification: 49-State



features

- INVERTER TECHNOLOGY - CLEAN, STABLE POWER
- LIGHTWEIGHT, COMPACT DESIGN
- ELECTRONIC OVERLOAD PROTECTION
- LED STATUS INDICATOR LIGHTS
- LOW-OIL SHUT DOWN.
- FLEXPPOWER FUEL MANAGEMENT SYSTEM
- DURABLE, FULLY ENCLOSED CASE

customer connections

Connection Outlets


A 2x5-15R

Circuit Breakers

M Internal Circuit Breakers

Other Features

H Flex Power



specifications

Product Series	iX800
Model	5791-0
Configuration/Emissions	49-State
A/C Rated Output Watts:	800
A/C Maximum Output Watts:	850
A/C Voltage	120VAC
A/C Frequency	60 Hz
Rated 120/240 VAC Amperage	6.6
Max 120/240 VAC Amperage	7.1
Engine Displacement	38cc
Engine Type	OHV
Engine RPM	Variable
Recommended Oil	SAE 30
Lubrication Method	Splash Sump
Choke Type	Manual Lever
Fuel Shut Off	Manual Lever
Idle Control	FlexPower
Starting Method	Manual
Battery	N/A
Battery Size	N/A
Low Oil Shutdown Method	Low Level

Start Switch Type	On/Off Toggle
Switch Location	On Engine
Single-Point Lifting Eye	N/A
Fuel Gauge	N/A
Fuel Tank Capacity (Gal)	0.50
Fuel Tank Capacity (Ltrs)	1.90
Run Time at 50% (Hours)	3.60
Cord Set	N/A
Handle Style	Fixed
Wheel type	N/A
Maintenance Kit	Sold Separately
Warranty - Residential	2 Year
Warranty - Commercial	6 Months

dimensions and weights

Length (L)	18.0
Width (W)	10.0
Height (H)	15.0
Extended Length (EL)	18.0
Carton Length	21.3
Carton Width	11.3
Carton Height	16.5
Unit Weight (lbs)	29.0
Shipping Weight (lbs)	33.0

