

# SNOWTHROWER Specifications

**Meet Your Match.** Whether you have an endless driveway or a small walkway, Toro has a snowthrower designed just for you. Check out all of the innovative features that make Toro the leader in snow removal—from self-propelled drive systems to handle-mounted controls. Engineered to perform and built to last, every Toro snowthrower is backed by Toro’s 2 Year Full Coverage Warranty. This winter, put a Toro to work for you.



Power Max



Power Throw

	Two-Stage <b>Power Max</b> <sup>®</sup>			<b>Power Throw</b> <sup>®</sup>	
<b>MODEL</b>	<b>826LE</b> 38622	<b>828LXE</b> 38630	<b>1028LXE</b> 38640	<b>11280XE</b> 38650	<b>522E</b> 38605
<b>Capacity/Minute*</b>	Up to 1900 lbs	Up to 2000 lbs	Up to 2100 lbs	Up to 2200 lbs	Up to 1800 lbs
<b>Throw Distance*</b>	Up to 45'	Up to 45'	Up to 45'	Up to 45'	Up to 30'
<b>Clearing Width</b>	26"	28"	28"	28"	22"
<b>Engine</b>	Tecumseh <sup>®</sup> Snow King <sup>®</sup> 4-Cycle	Tecumseh Snow King 4-Cycle	Tecumseh Snow King 4-Cycle	Tecumseh Snow King OHV 4-Cycle	Tecumseh <sup>®</sup> Snow King <sup>®</sup> 4-Cycle
<b>Horsepower^/ Displacement</b>	8 hp	8 hp	10 hp	11 hp	5 hp
<b>Starter</b>	120 Volt Electric	120 Volt Electric	120 Volt Electric	120 Volt Electric	120 Volt Electric
<b>Fuel Capacity</b>	1 Gallon	1 Gallon	1 Gallon	1 Gallon	2 Quarts
<b>Ignition</b>	Electronic	Electronic	Electronic	Electronic	Electronic
<b>Compression Release</b>	Standard	Standard	Standard	Standard	Standard
<b>Governor</b>	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
<b>Auger System</b>	Power Max <sup>®</sup>	Power Max	Power Max	Power Max	Power Throw <sup>®</sup>
<b>Auger Size</b>	14" Serrated	14" Serrated	14" Serrated	14" Serrated	12"
<b>Chute Control</b>	Quick Stick <sup>®</sup>	Quick Stick	Quick Stick	Quick Stick	Remote Chute Crank
<b>Drive System</b>	Friction Disc	Friction Disc with Freewheel Steering	Friction Disc with Freewheel Steering	Friction Disc with Freewheel Steering	Friction Disc
<b>Speeds</b>	6 Forward 2 Reverse	6 Forward 2 Reverse	6 Forward 2 Reverse	6 Forward 2 Reverse	3 Forward 1 Reverse
<b>One-Hand Interlock</b>	Standard	Standard	Standard	Standard	N/A
<b>Tires</b>	15" x 5"	15" x 5"	15" x 5"	15" x 5"	13" x 5"
<b>Light</b>	Standard	Standard	Standard	Standard	N/A
<b>Skid Shoes</b>	Reversible	Reversible	Reversible	Reversible	Standard
<b>Scraper</b>	Adjustable	Adjustable	Adjustable	Pivoting	Adjustable
<b>Snow Cut Depth – 1 Pass</b>	21"	21"	21"	21"	17.5"
<b>Weight</b>	234 lbs	249 lbs	249 lbs	257 lbs	143 lbs
<b>Warranty**</b>	2 Year Full Coverage Pick Up and Delivery	2 Year Full Coverage Pick Up and Delivery	2 Year Full Coverage Pick Up and Delivery	2 Year Full Coverage Pick Up and Delivery	2 Year Full Coverage Pick Up and Delivery
<b>ACCESSORIES</b>					
<b>Tire Chains</b>	Optional	Optional	Optional	Optional	Optional
<b>Snow Cab</b>	Optional	Optional	Optional	Optional	Optional
<b>Drift Breaker</b>	Optional	Optional	Optional	Optional	Optional



CCR Powerlite



CCR 2450 GTS



Power Clear

Single-Stage	Compact <b>Powerlite®</b>	<b>Power Curve®</b>	<b>Power Clear™</b>		
<b>MODEL</b>	<b>CCR™ Powerlite®</b> 38172/38182	<b>CCR™ 2450 GTS®</b> 38515	<b>221R/E</b> 38581/38582	<b>221QR/QE</b> 38583/38584	<b>421QR/QE</b> 38585/38586
Capacity/Minute*	Up to 1100 lbs	Up to 1700 lbs	Up to 1700 lbs	Up to 1700 lbs	Up to 1800 lbs
Throw Distance*	Up to 25'	Up to 30'	Up to 30'	Up to 30'	Up to 35'
Clearing Width	16"	20"	21"	21"	21"
Engine	Tecumseh® 2-Cycle	Toro R*tek® 2-Cycle	Toro R*tek 2-Cycle	Toro R*tek 2-Cycle	Tecumseh 5.5 hp <sup>^</sup> 4-Cycle
Displacement	98 cc	141 cc	141 cc	141 cc	195 cc
Starter	Recoil or 120 Volt Electric	Recoil	Recoil or 120 Volt Electric	Recoil or 120 Volt Electric	Recoil or 120 Volt Electric
Fuel Capacity	0.9 Quarts	1.0 Quarts	1.1 Quarts	1.1 Quarts	1.1 Quarts
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic
Compression Release	Standard	Standard	Standard	Standard	Standard
Governor	Air-Vane	Air-Vane	Air-Vane	Air-Vane	Mechanical
Auger System	Power Curve System	Power Curve System	Power Curve System	Power Curve System	Power Curve System
Auger or Rotor Type	Rubber Paddles	Rubber Paddles	Rubber Paddles	Rubber Paddles	Rubber Paddles
Chute Control	Chute and Deflector Handle	Chute and Deflector Handle	Chute Handle and Zip Deflector	Quick Shoot with Zip Deflector	Quick Shoot with Zip Deflector
Drive System	Rotor Propelled	Rotor Propelled	Power Propel Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel
Tires	6" x 1.5"	7" x 1.5"	7" x 1.5"	7" x 1.5"	7" x 1.5"
Folding Handle	Standard	Ergonomic	Standard	Standard	Standard
Cut Depth – 1 Pass	11"	13"	12.5"	12.5"	12.5"
Weight with Electric	39 lbs	74 lbs	74 lbs	76 lbs	83 lbs
Weight with Recoil	37 lbs	71 lbs	72 lbs	74 lbs	78 lbs
Warranty**	2 Year Full Coverage	2 Year Full Coverage 5 Year Guaranteed To Start	2 Year Full Coverage 5 Year Guaranteed To Start	2 Year Full Coverag 5 Year Guaranteed To Start	2 Year Full Coverage 5 Year Guaranteed To Start

Electric **Power Shovel / 1800 Power Curve®**



Power Shovel



1800 Power Curve

<b>MODEL</b>	<b>Power Shovel</b> 38361	<b>1800 Power Curve</b> 38025
Throw Distance*	Up to 20'	Up to 30'
Capacity/Minute*	Up to 300 lbs	Up to 700 lbs
Clearing Width	12"	18"
Snow Cut Depth – 1 Pass	6"	10"
Time To Clean 4" of Snow Off a 50' x 20' Driveway	20 Minutes	10 Minutes
Directional Control	N/A	180° Adjustable Chute with Deflector
Double Insulated UL Listed	Yes	Yes
Motor Type and Amp	Series-Wound 7.5 Amp	Series-Wound 12.0 Amp
Drive System	Poly-V Belt	Poly-V Belt
Rotor Style	Single Piece, 2-Blade, Curved Rotor	Single Piece, 2-Blade, Curved Rotor
Weight	13 lbs	24 lbs
Warranty**	2 Year Full Coverage	2 Year Full Coverage

➡ = Step Up Feature

\* Capacity and throw distance will vary with conditions.

\*\* See retailer for full warranty details or go to [www.toro.com](http://www.toro.com).

<sup>^</sup> The gross horsepower of this engine was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission, and operating requirements, the actual engine horsepower on this class of snowthrower will be significantly lower.

Specifications, design and accessories subject to change without notice.

We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation.

Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

Snow King is a registered trademark of Tecumseh®.